

# RM243 New!

## 2U Compact Server Chassis



### Features & Benefits

- Optional Front I/O or Rear I/O chassis
- Support Extended ATX (12" x 13") M/B
- Optional slim CD-ROM
- Support standard or low profile rear window
- Flexible HDD allocation

## Specification

### RM24302

<b>Model Name</b>	• RM24302
<b>Standard</b>	• EIA-RS310D
<b>M/B Form Factor</b>	• Extended ATX (12"x13"), CEB (12" x 10.5"), ATX (12" x 9.6")
<b>Dimension (D×W×H)</b>	• 406 mm × 430 mm × 88 mm • 16" × 16.9" × 3.5"
<b>Drive Bay</b>	• Internal : 3.5" : 2 (Optional) • Slim CD-ROM : 1 (Optional) • Hot-Swap HDD Tray : 2
<b>PSU</b>	• Form Factor : Single • Watt : 600 W
<b>Indicator</b>	• 1 x Power Status LED, 1 x HDD Activity LED, 2 x LAN Activity LEDs, 1 x Fan Failure & Overheat Warning
<b>Front Control</b>	• Power ON/OFF, Alarm Mute, System Reset, 2 x USB 2.0 Ports
<b>System Security</b>	• N/A
<b>Cooling Fan</b>	• Front : 3 x 80 mm (T=32 mm) middle fans • Middle : N/A • Rear : N/A
<b>Slot Opening</b>	• 3 x full height or 6 x low profile
<b>Plastic Material Type</b>	• ABS-HB
<b>Sheet Metal Material Thickness</b>	• SGCC/1.2 mm
<b>Net Weight (Chassis only)</b>	• 6.9 Kg
<b>Backplane</b>	• SATAII/SAS
<b>Rear Window</b>	• Low Profile or Standard
<b>Front Bezel</b>	• N/A
<b>Cubic Feet</b>	• 3.05
<b>Container Info. (Single Packing)</b>	• 20' : 416 • 40' : 840

## Feature

### RM24302

